

TYR-T

Industrial shock cooler

General information & application

Industrial shock coolers Helpman TYR-T have been specifically designed for application in cooling and freezing tunnels. Shock-cooling is a process by which a product, mostly meat, is cooled quickly but not too deeply. The principle of shock-cooling is that the surface of the meat product is cooled until just below the freezing point, so that the surface becomes vapour-tight. This has the purpose of limiting the weight (moisture) loss of the product to a minimum. The product may not be cooled too deeply however, since otherwise the structure of the underlying tissue is damaged, resulting in a decline of the quality of the meat. For shock-coolers, it is important that the total surface of the product that is to be cooled be fully exposed to the cold air flowing from the cooler. For this reason, all models are characterised by an elevated external pressure (120 Pa).

Evaporating temp.	+5 to -40 °C
Refrigerants	ammonia (R-717), all H(C)FC, brine, CO ₂
Capacities (SC2)	11 up to 114 kW*
Air volume	11,800 up to 66,400 m ³ /h.

* Higher capacities on request

Standard configuration

- Finned coil
 - 2 coil block modules
 - 4, 6 or 8 tube rows deep
 - Stainless steel tubing \varnothing 16 mm
 - Tube pitch 50 x 50 mm square
 - Corrugated Alu-fins
 - Fin spacings 7 or 10 mm.
- 2, 4, 6 or 8 Fans, blowing through the coil.
Diameters \varnothing 508 mm or \varnothing 560 mm. Enclosed design spray-tight fan motors, protection class IP55. Motors are equipped with a thermal safety device in the windings, connected to separate terminals in the box.
- Fans with elevated external pressure (120 Pa).
- Corrosion resistant casing material:
Aluminium/Senzimir, white epoxy coated (RAL 9003).
- Hinged, enclosed end covers.



TYR-T

- Hinged drip tray, drain(s) 32 mm PVC connection, freely adjustable into either horizontal or vertical position.
- Refrigerant distribution optimised to refrigerant applied.
- Refrigerant connections on right hand side (fan side view).
- Fitted with schröder valve on the suction connection for testing purposes. (not for R-717).
- Sufficient room for fitting the expansion valve inside.
- Suitable for dry expansion or pumped system.
- Stickers indicate fan direction and refrigerant in/out.
- Delivery in mounting position. Coolers are mounted on wooden beams. Installation can take place with use of a forklift.

Design pressure

Design pressure 33 bar (H(C)FC), 27 bar (ammonia) or 6 bar (brine). Higher design pressures on request. Each heat exchanger is leak tested with dry air and finally supplied with a nitrogen pre-charge.

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана +7(7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395) 279-98-46

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93


Киргизия (996)312-96-26-47

Казахстан (772)734-952-31

Таджикистан (992)427-82-92-69

Эл. почта: afm@nt-rt.ru || Сайт: <http://alfa-laval.nt-rt.ru>

Options

- Defrost systems
 - Hot gas coil in driptray (G1, G2)
 - Hot gas connected (G1C, G2C)
 - Hot gas coil in driptray connected to suction header, without non-return valve.*
 - Electric defrost (E1, E2, E4)
 - Water defrost (W)
 - Electric defrost for air coolers with pumped refrigerant circulation or in glycol execution on special request only.*
- Driptray insulation
 - Styropore 10 mm + cladding (I 2)
 - Not combined with electric defrost*
 - Foamglass 25 mm + cladding (I 3)
- Refrigerant connections (L / R) (fan side view)
 
- Isolating switch, mounted (ISM)
- Fan ring heater 230 V (FRH)
- Secondary refrigerant
 - All models available for water/glycol application. Standard stainless steel welding connections, other connections (thread/flange) on request.*
- Stainless steel 304 casing (SSC)
- Hinged fan plate (HN)
- Fan motors 254-280/440-480/60/3 or 230/60/1

Code description

TYR-T	3	4	6	7	H1/6	400	-	Options
1	2	3	4	5	6	7		8

- Industrial shock cooler stainless steel/aluminium
- Cooler module (3 and 4)
- Number of fans (3 to 7)
- Tube rows in air direction (4, 6 or 8)
- Fin spacing (7 or 10 mm)
- Circuiting design (2H, H1, H2 ...)
- Fan power supply (400=230/400/50/3, 230=230/50/1)
- Option codes

Non-standard executions (on request only)

- Higher capacities
- Special fan motors
 - Dual fan speed motors
 - Variable fan speed motors
 - EC fans
 - Alternative electrical supply 230-380/60/3
- Built in heater coil sections

Selection

Selection and pricing is to be performed with our Alfa Laval air heat exchanger selection software. Selection output includes all relevant technical data and dimensional drawings. Please contact our sales organization for details and full technical documentation.

Benefits

- Application based air cooler design to secure product quality.
- Elevated external fan pressure to ensure optimised air flow around the product.
- Advanced product selection software available.
- Heavy duty coil & casing materials, resulting in a long operational product life.
- Reliable performance.
- Easy-install.
- Energy efficient.
- Low defrost frequency thanks to square tube pitch configuration.
- Low total cost of ownership.
- Two-year product guarantee.
- Easy access to additional on-line product information (QR code)